

EVERUN ER 08/811, 2025 mod



Kr.: 189.900 ex. mva

Standard utstyr:

- Standard skuffe
- Joystick, mekanisk med gir, høy og lavserie
- Konstant firehjulsdrift med konverter
- Quick shift av redskap, Trima feste
- Hydraulisk converter
- Euro V standard motor,
- Flyt funksjon,
- Ekstra hydraulikk, totalt fire funksjoner
- Kjøre/arbeidslys forover og bakover
- Luksus hytte, med ryggekamera og varmeapparat
- Justerbart ratt og sete med setebelte
- Hydrauliske trommelbremsere alle hjul og park brems
- Dekk 31/15,5-15
- Lås for løft og styresylinder
- Hydraulisk trykk sjekk system
- Varta batteri type vinter
- Hovedstrøms bryter
- Motorvarmer

Tilbehørsliste:

| | |
|--|---------------|
| - Mekaniske pallegafler | Kr.: 7.900,- |
| - Hydrauliske pallegafler | Kr.: 15.900,- |
| - Snøskjær, hydraulisk, rett 2 m | Kr.: 24.900,- |
| - Hydraulisk snøskjær med V-blad | Kr.: 26.900,- |
| - Snøskuffe | Kr.: 7.900,- |
| - Snøskuffe med hydrauliske vinger, 3m | Kr.: 24.900,- |
| - 4 i 1 skuffe | Kr.: 12.900,- |
| - Blandeskuffe (Mixer bucket) | Kr.: 14.900,- |
| - Sandskuffe | Kr.: 7.900,- |
| - Gripeskuffe | Kr.: 10.900,- |
| - Dekk type gress 33/15,5-16,5 | Kr.: 9.900,- |
| - Dekk 12-16,5 | Kr.: 8.900,- |
| - Kjettinger pr par | Kr.: 6.900,- |
| - Sandspreder front | Kr.: 34.900,- |
| - Sandspreder bak m/hydraulikk | Kr.: 39.900,- |
| - Tømmerklo 360 grader | Kr.: 29.900,- |
| - Feiemaskin | Kr.: 26.900,- |
| - Feiemaskin med oppsamler | Kr.: 29.900,- |
| - Feiemaskin med vanntank | Kr.: 34.900,- |
| - Jordbor 200mm | Kr.: 15.900,- |
| - Jordbor 300mm | Kr.: 17.900,- |
| - Rundballeløfter | Kr.: 14.900,- |
| - Oljefatløfter | Kr.: 14.900,- |

Spesifikasjoner

1.0 Engine Details

| | |
|---|---|
| (1) Model: | Changchai Euro V |
| (2) Engine Type: | 4 cyl commonrail, Water-cooled, Diesel Engine |
| (3) Rated Power: | 18 KW |
| (4) Rated Speed: | 2500 r/min(rpm) |
| (5) Fuel Consumption Ration in Standard Working Condition | 252 g/kw.H |

2.0 Transmission System

| | |
|-------------------------------------|---------------------------|
| (1) Type: | Fixed-spindle Power Shift |
| (2) Shift Gear Control Oil Pressure | 1.0-1.8MPa |
| (3) Rated Input Speed | 2500(rpm) |

3.0 Bucket

| | |
|----------------------|--------------------------|
| (1) Bucket Capacity: | 0.48 m ³ |
| (2) Bucket Width: | 1700mm |
| (3) Bucket Type: | Heavy-duty Bolt on Teeth |
| (4) Rated Load: | 800kg |
| (5) Net Weight | 2700kg |

4.0 Overall Dimensions

| | |
|---------------------------------------|--------|
| (1) Overall Length(bucket on ground); | 4620mm |
| (2) Overall Height ; | |
| (3) Ground to Cab Top: | 2540mm |
| (4) Dumping Height: | 2120mm |
| (5) Min. Base to the Ground | 220mm |
| (6) Overall Width | 1500mm |

5.0 Operating Specifications

| | |
|--------------------------|---|
| (1) Steering System: | Articulated Frame with Hydraulic Power Steering |
| (2) Min. Turning Radius: | 5200mm |
| (3) Driving System: | Hydraulic Converter |

6.0 Brake System

| | |
|-------------------|---|
| (1) Service Brake | Four wheel Hydraulic Spread-shoed Brake |
| (2) Parking Brake | Hand Operated |

