

EVERUN ER 12



Kr.: 124.900 ex. mva

Standard utstyr:

- Standard skuffe**
- Joystick med gir, høy og lavserie**
- Konstant firehjulsdrift**
- Quick shift av redskap**
- Hydraulisk converter, forover og bakover med spaker**
- Euro III standard motor, 50 hk**
- Flyt funksjon,**
- Ekstra hydraulikk, totalt fire funksjoner**
- Kjøre/arbeidslys forover og bakover**
- Luksus hytte, tiltbar med ryggekamera og varmeapparat**
- Justerbart ratt og sete med setebelte**
- Hydrauliske skivebremse alle hjul og park brems**
- Dekk 20,5/70-16**
- Lås for løft og styresylinder**
- Hydraulisk trykk sjekk system**
- Varta batteri type vinter**
- Hovedstrøms bryter**
- Motorvarmer**

Tilbehørsliste:

- Mekaniske pallegafler	Kr.: 5.900,-
- Hydrauliske pallegafler	Kr.: 10.900,-
- Snøskjær, hydraulisk, rett	Kr.: 11.900,-
- Hydraulisk snøskjær med V-blad	Kr.: 16.900,-
- Snøskuffe	Kr.: 9.900,-
- Snøskuffe med hydrauliske vinger, 3m	Kr.: 17.900,-
- 4 i 1 skuffe	Kr.: 12.900,-
- Blandeskuffe (Mixer bucket)	Kr.: 12.900,-
- Sandskuffe	Kr.: 7.900,-
- Gripeskuffe	Kr.: 10.900,-
- Dekk type vinter 315/80 R22,5	Kr.: 15.000,-
- Dekk type gress	Kr.: 10.900,-
- Kjettinger pr par	Kr.: 4.900,-
- Sandspreder front	Kr.: 15.900,-
- Sandspreder bak m/hydraulikk	Kr.: 21.900,-
- Tømmerklo 360 grader	Kr.: 17.900,-
- Feiemaskin	Kr.: 19.900,-
- Feiemaskin med oppsamler	Kr.: 21.900,-
- Feiemaskin med vanntank	Kr.: 26.900,-
- Jordbor 200mm	Kr.: 15.900,-
- Jordbor 300mm	Kr.: 17.900,-
- Rundballeløfter	Kr.: 9.900,-
- Oljefatløter	Kr.: 9.900,-

Spesifikasjoner

1.0 Engine Details

(1) Model:	Xinchai 490 BPG(EuroIII Standard)
(2) Engine Type:	In-line Arrangement, Water-cooled, Four-cycle Diesel Engine
(3) Rated Power:	36.8 KW
(4) Rated Speed:	2650 r/min(rpm)
(5) Fuel Consumption Ration in Standard Working Condition	252g/kw.H

2.0 Transmission System

(1) Type:	Fixed-spindle Power Shift
(2) Shift Gear Control Oil Pressure	1.0-1.8MPa
(3) Rated Input Speed	2500(rpm)

3.0 Bucket

(1) Bucket Capacity:	0.53 m ³
(2) Bucket Width:	1740mm
(3) Bucket Type:	Heavy-duty Bolt on Teeth
(4) Rated Load:	1200kg
(5) Operating Weight	3400kg

4.0 Overall Dimensions

(1) Overall Length(bucket on ground);	5200mm
(2) Overall Height ;	
(3) Ground to Cab Top:	2550mm
(4) Dumping Height:	2450mm
(5) Min. Base to the Ground	240mm
(6) Overall Width	17400mm

5.0 Operating Specifications

(1) Steering System:	Articulated Frame with Hydraulic Power Steering
(2) Min. Turning Radius:	5200mm
(3) Driving System:	Hydraulic Converter

6.0 Brake System

(1) Service Brake	Four wheel Hydraulic Spread-shoed Brake
(2) Parking Brake	Hand Operated

