

EVERUN ER 25



Kr.: 229.900 ex. mva

Standard utstyr:

- Standard skuffe
- Elektrisk joystick med gir, høy og lavserie
- Konstant firehjulsdrift og reduksjons nav
- Quick shift av redskap
- Hydraulisk converter
- Euro III standard motor, 95 hk
- Flyt funksjon,
- Ekstra hydraulikk, totalt fire funksjoner
- Led kjøre/arbeidslys forover og bakover
- Luksus hytte, tiltbar med ryggekamera og varmeapparat
- Justerbart ratt og sete med setebelte
- Hydrauliske skivebremse alle hjul og park brems
- Dekk 16/70-20
- Lås for løft og styresylinder
- Hydraulisk trykk sjekk system
- Varta batteri type vinter
- Hovedstrøms bryter
- Motorvarmer

Tilbehørsliste:

- Hydrauliske pallegafler	Kr.: 12.900,-
- Snøskjær, hydraulisk, rett	Kr.: 10.900,-
- Hydraulisk snøskjær med V-blad	Kr.: 16.900,-
- Snøfreser, hydraulisk	Kr.: 22.900,-
- Snøskuffe	Kr.: 8.900,-
- Snøskuffe med hydrauliske vinger, 3m	Kr.: 16.900,-
- 4 i 1 skuffe	Kr.: 11.900,-
- Blandeskuffe (Mixer bucket)	Kr.: 14.900,-
- Sandskuffe	Kr.: 6.900,-
- Gripeskuffe	Kr.: 9.900,-
- Kjettinger pr par	Kr.: 4.900,-
- Sandspreder front	Kr.: 14.900,-
- Sandspreder bak m/hydraulikk	Kr.: 21.900,-
- Tømmerklo 360 grader	Kr.: 17.900,-
- Feiemaskin	Kr.: 15.900,-
- Feiemaskin med oppsamler	Kr.: 17.900,-
- Feiemaskin med vanntank	Kr.: 22.900,-
- Jordbor 200mm	Kr.: 15.900,-
- Jordbor 300mm	Kr.: 17.900,-
- Rundballeløfter	Kr.: 8.900,-
- Oljefatløter	Kr.: 8.900,-

Spesifikasjoner

1.0 Engine Details

(1) Model:	Xinchai 4DX22-96(EuroIII Standard)
(2) Engine Type:	In-line Arrangement, Water-cooled, Four-cycle Diesel Engine
(3) Rated Power:	70.0 KW
(4) Rated Speed:	2500 r/min(rpm)
(5) Fuel Consumption Ration in Standard Working Condition	260g/kw.H

2.0 Transmission System

(1) Type:	Fixed-spindle Power Shift
(2) Shift Gear Control Oil Pressure	1.0-1.8MPa
(3) Rated Input Speed	2500(rpm)

3.0 Bucket

(1) Bucket Capacity:	0.72 m ³
(2) Bucket Width:	20400mm
(3) Bucket Type:	Heavy-duty Bolt on Teeth
(4) Rated Load:	2500kg
(5) Operating Weight	5200kg

4.0 Overall Dimensions

(1) Overall Length(bucket on ground);	5710mm
(2) Overall Height ;	
(3) Ground to Cab Top:	2840mm
(4) Dumping Height:	2850mm
(5) Min. Base to the Ground	275mm
(6) Overall Width	2040mm

5.0 Operating Specifications

(1) Steering System:	Articulated Frame with Hydraulic Power Steering
(2) Min. Turning Radius:	5460mm
(3) Driving System:	Hydraulic Converter

6.0 Brake System

(1) Service Brake	Four wheel Hydraulic Spread-shoed Brake
(2) Parking Brake	Hand Operated

